



# GEMINI

ULTRA HIGH-PURITY WATER SYSTEM

## KEY FEATURES

- UP TO 3.7 LITERS PER MINUTE OF 18 MEGOHM WATER
- AUTOMATIC PROGRAMMABLE FILLING
- MULTI-PASS UV STERILIZATION

## GEMINI-MB SYSTEM

The GEMINI Ultra High Purity Water System provides up to 3.7 liters per minute of 18.2 megohm, 0.2 micron filtered water. The Multi-Pass Ultraviolet system irradiates the water at three separate passes in the recirculation loop. The dispensing port is continuously exposed to UV for complete sterility at the outlet. Water quality meets or exceeds ASTM, CAP and NCCLS Type 1 specifications.

Controls include PLC and a 3.5" high resolution HMI display. Touch panel screen provides easy interface for dispensing and programming up to four batches. Resistivity is clearly displayed with system operation status. Display turns red during alarm condition below resistivity set point. Hibernation mode runs the pump intermittently to keep the system ultrapure.


The integral basin accommodates filling large containers and controls drips and spills. A variety of options are available such as a dispensing gun, ultra-filtration, wall mounting hardware and a sanitization kit. RO pretreatment systems are also available.



## FEATURES & BENEFITS


- **MICROPROCESSOR CONTROLLED**  
Intuitive touch screen allows for programmable dispensing of 18.2 megohm water into various containers at the touch of a button.
- **MULTI-PASS UV STERILIZATION**  
Continuous recirculation ensures water quality is maintained before it passing through the UV sterilized dispensing port.
- **ULTRAPURE WATER**  
Exceeds ASTM, CAP and NCCLS Type I specifications and meets bio-medical grade specification ASTM D5196.
- **ISO 9001 : 2008 CERTIFIED**

## FLOW DIAGRAM



# GEMINI ULTRA HIGH-PURITY WATER SYSTEM

## TECHNICAL DATA



### Dimensions (H x W x D)

21.5 in. x 18.25 in. x 18.25 in.  
(61 cm x 46 cm x 47 cm)

### Weight

42 lbs. dry / 47 lbs operating  
(22.7 kg dry / 25 kg operating)

### Inlet Connection

3/8" O.D. Tubing  
.375 mm O.D. Tubing

### Power Requirements

120 VAC/ 60 Hz @ 1.0 amp

### Pressure

90 PSIG Maximum  
20 PSIG Minimum

### Temperature (Max.)

100 °F  
30 °C

### Flow Rate

1.0 Gallons Per Minute  
3.7 Liters Per Minute

### Outer Shell

Polypropylene  
316 Stainless Steel

## INFLUENT QUALITY

Source	Reverse Osmosis, DI, or Distillation
Purity	< 20 $\mu$ S/cm
Filtration	0.2 $\mu$ m
Free Chlorine	< 0.05 ppm
Silica	< 2 ppm
TOC	< 50 ppb

## EFFLUENT QUALITY (STANDARD SYSTEM)

Standard System-	
Purity	> 18 Megohm-cm
Microorganisms	< 10 CFU / 1000 ml
Chlorides	< 1 ppb
Sodium	< 1 ppb
With 0.05 micron UF- Endotoxin	< 0.03 EU
With Combination UV / TOC Destruct- TOC	< 3 ppb

## ORDERING GUIDE

GMB-102	110 VAC Unit w/ 0.2 $\mu$ Filter
GMB-105	110 VAC Unit w/ 0.05 $\mu$ m Ultra Filter

## OPTIONS & ACCESSORIES

GMA-DG	Dispensing gun and tubing kit
GMA-UV	U.V. Combination for bacteria and TOC destruct
GMA-DF	Direct feed
GMA-WB	Wall mounting bracket
AFK-002	Cartridge Kit w/ (2) high purity cartridges
AFK-006	Cartridge Kit with (2) low TOC Deionization Cartridges and 10-inch 0.2 micron filter
AFK-008	Cartridge Kit with (3) high purity Low TOC Cartridges and (1) 0.05 $\mu$ ultrafilter
AFK-009	Cartridge Kit with (3) high purity Low TOC Cartridges
PF-00-6505	In-Line Hollow Fiber 0.05 micron UF for pyrogen removal
HPA-005	Sanitization Kit
HPA-008	220 VAC external power converter
HPL-RO	Reverse Osmosis pretreatment

## MADE IN USA

PROUD TO BE  
ISO 9001 : 2008 CERTIFIED



Note: Ordering information subject to change without notice. Please verify all specifications prior to ordering.  
For more information Call: (856) 626-1550

### IMPORTANT NOTICE TO USER:

The following is made in lieu of all other warranties expressed or implied. Manufacturer's and Seller's only obligation shall be to issue credit against the purchase or replacement of the equipment proved to be defective in material or workmanship. Neither Manufacturer nor Seller shall be liable for any injury, loss or damage, direct or indirect, special or consequential, arising out of the use of, misuse, or the inability to use such product. The information contained herein is based on technical data and tests which we believe to be reliable and is intended for use by persons having technical skill at their discretion and risk. Since conditions of use are outside ResinTech's control, we can assume no liability whatsoever for results obtained or damages incurred through the application of the data presented. This information is not intended as a license to operate under, or a recommendation to infringe upon, any patent of ResinTech's or others covering any material or use. The foregoing may not be altered except by written agreement signed by officers of the manufacturer.

Gemini - 052213